

FIRE ALARM SYSTEMS.
POWERED BY PARTNERSHIP.*

CONVENTIONAL 2-WIRE SMOKE & HEAT DETECTORS

KC2 SERIES

OVERVIEW

The Kidde conventional photoelectric smoke and heat detectors are interchangeable head and base detectors using Optica smoke sensing technology and high accuracy heat sensor that provides outstanding stability and excellent response to a wide range of fires.

Like their Kidde Intelligent series counterparts, KC2 smoke detectors feature a photoelectric chamber using Optica sensing technology providing multi criteria response discriminating real smoke from other nuisance sources. A single tri-color LED located on the housing provides alarm, trouble and standby indications.

The KC2 series consist of 3 models; KC2-OS is a multi criteria photoelectric smoke detector delivering a wide sensitivity range with discrimination to nuisance events and built in environmental compensation.

KC2-OSH is a multi criteria photoelectric smoke and heat detector delivering a wide sensitivity range with discrimination to nuisance events and built in environmental compensation but also includes a heat sensor with a 135 fixed threshold and rate of rise compensation.

KC2-H is a heat only detector comprised of a heat sensor with a 135 fixed threshold and rate of rise compensation.

KC2 series detectors are complimented by a range of standard and relay bases for a variety of electrical box applications.

And, if they become dirty over time, the KC2 Series detectors automatically adjust the alarm threshold through built-in drift compensation.



Smoke, Heat, and Nuisance Alarms
UL 268 7th Ed.



7270-1657-0523
7272-1657-0524

STANDARD FEATURES

- Self-diagnostic capability continually monitors operation
- Meets NFPA 72 sensitivity test requirements
- Head and terminal base design (base sold separately)
- Automatic drift compensation
- Tri-color status LED, solid red for alarm, flashing yellow for trouble and flashing green for standby
- Low-profile design blends into the ceiling
- Advanced nuisance discrimination from non fire sources like cooking smoke and non condensing water vapor

ENGINEERING SPECIFICATIONS

The Kidde KC2 Series photoelectric smoke detector, is a low profile, self-diagnostic, two-wire detector that monitors its own sensitivity and operational status. The detector meets NFPA 72 field sensitivity testing requirements without the need for external meters. Built-in drift compensation automatically adjust the sensitivity if the detector gets dirty. Normal sensing occurs every 2 seconds. A sophisticated algorithm is started when a signal exceeding the alarm threshold value is sensed. To prevent nuisance conditions, multiple LED wavelengths and angles are used to determine alarm from real smoke conditions above the threshold level initiate an alarm. The patented optical sensing chamber oriented downward to sample air flow allowing for less maintenance and easy cleaning.

*Kidde Commercial and its authorized resellers/distributors are separate and independent entities. This relationship between vendor and reseller/distributor does not constitute a legal partnership or create any shared liability between companies.



FIRE ALARM SYSTEMS.
POWERED BY PARTNERSHIP.*

CONTACT US

Phone: 888.244.9979 (Option 4)
Email: kidde.fire@kgsolutions.com
Website: kidde-esfire.com

8985 Town Center Pkwy,
Bradenton, FL 34202

©2025 Walter Kidde Portable Equipment, LLC
All rights reserved.

*Kidde Commercial and its authorized resellers/
distributors are separate and independent entities.
This relationship between vendor and reseller/
distributor does not constitute a legal partnership
or create any shared liability between companies.

TECHNICAL SPECIFICATIONS

Electrical

Voltage	6.5 — 33VDC
Maximum ripple (peak to peak)	10% (Vp - p)
Typical standby current (24V)	88µA
Typical alarm current	up to 60 mA max, if not limited by control panel
Photoelectric Sensitivity	0.5% to 4.36%/ft
Operating temperature	32°F to 120°F (0°C to 49°C) for photo 32°F to 100°F (0°C to 38°C) for Heat & Photo/Heat
Operating humidity range	0 to 95% Non-condensing
RFI immunity	20 V/m min; 0-1000 MHz
Remote LED output current	5 mA min, 8.5 mA max
Drift compensation adjustment	1.0%/ft. max
Compatibility	FX5, FX10, GSA-UM/MAB, RZ116-2, RZ116-2RS, FX-2WIRE

Environmental

Heat Sensor Ratings (KC2-H & KC2-OSH)	Fixed 135°F/ Rate of rise 15°F/min., >105°F (8.3°C/min., >40.6°C), FM response - Quick
Maximum wind velocity	0 to 300 ft/min
Field wiring size	12-18 AWG
Reset voltage	2.5V max
Reset time	1 second max
UL two-wire compatibility identifier	S10A

Physical

Color	White head and base
Detector head dimensions	4" D x 1.75" H (10 cm x 4.44 cm)

Regulations

Listing	UL 268 7th ed, ULC, FM, CSFM
---------	------------------------------

ORDERING INFORMATION

Model	Description	Ship wt. lbs (kg)
KC2-OS	Smoke detector head only, photoelectric, two-wire	0.4 (0.16)
KC2-OSH	Smoke & Heat detector head only, photoelectric, two-wire w/integral 135 heat	0.4 (0.16)
KC2-H	Heat detector head only, 135 fixed/ROR	0.4 (0.16)
KC2-SB	Standard base, 4 terminals, 4" dia.	0.2 (0.09)
KC2-SB4	Standard base w/trim skirt, 4 terminals, 6" dia.	0.2 (0.09)
KC2-RB	Relay base, 4 terminals, aux. relay, 4" dia.	0.2 (0.09)
KC2-RB4	Relay base w/trim skirt, 4 terminals, aux. relay, 6" dia.	0.2 (0.09)
GSA-LED	Remote Indicator, single gang, white	0.2 (0.09)
GSA-TS	Trim Skirt (optional for non 4" bases	0.1 (0.04)
SIGA-VA	Detector Cleaning Tool	0.2 (0.09)
SIGA-RTA	Detector Removal tool	0.2 (0.09)