



5MP HD-TVI IR Bullet Camera with Junction Box

V5B3M

2.8-12mm fixed lens, white housing

Features

- Supports up to 5MP @20FPS
- Up to 4x optical zoom
- IR Distance: 165' (depending on scene reflection)
- DWDR
- Motorized lens with auto focus
- 12VDC Operation (power supply not included)
- IP67 weather resistance

NDAA
COMPLIANT



Junction Box Included



Camera Specifications

Image Sensor	Progressive scan 1/2.5" CMOS
Resolution	5MP 2944 x 1656 (16:9)
Video Output	AHD/TVI/CVI/CVBS (*camera comes defaulted to HD-TVI)
Image System	PAL/NTSC
Electronic Shutter Speed	Auto; 1/50s-1/100000s(PAL); 1/60s-1/100000s (NTSC)
Minimum Illumination	Color: 0.01lux @ F1.2(AGC ON); B/W: 0 lux @ IR ON
S/N Ratio	≥ 52dB (AGC OFF)
Function Control	OSD (UTC Control)
Day/Night	✓
WDR	✓
DNR	✓
Gain Control	Auto
White Balance	ATW
Defog	X
BLC	✓
LSC	✓
Mirror	✓
Sharpness	✓
Smart IR	✓
Image Setting	✓
Defect Correction	Auto

Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	IR OFF ≤ 1W; IR ON ≤ 6W
Operating Temperature	-22°F - 122°F
Relative Humidity	10% - 90%
Unit Dimensions	8.6"(H) x 3.2"(W) x 3.2"(H)
Unit Weight	2.46lbs

Optional Accessories



PSW5
12VDC
Power Supply



CMT1
Corner Mount



PMT1
Pole Mount



FMT1
Flush Mount



CLT2J
Ceiling Mount



O5VLWMJ
Wall Mount



CLTX1
Ceiling Mount
4" Extension

NDAA
COMPLIANT

Products are in compliance with NDAA Section 889 Part B Guidelines. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 8/29/24