Cable

Datasheet
SM5220-3M
3 Meter 10G SFP+ Direct Attach Cable

Highlights

- 10G SFP+ connector on both sides
- Drives 10 Gigabit Ethernet (3m distance)



Overview

With a passive twin-ax cable assembly of 3 meters and two SFP+ connectors on each side, SM5220-3M is suitable for short distances and offers a cost-effective way to connect within racks and across adjacent racks.

Specifications

Hardware Features & Performance		
Model		SM5220-3M
General	Product Dimensions	• Plug: 2.26*0.53*0.34 in (57.5*13.55*8.55 mm); • Overall length: 118.11 in (3,000 mm)
	Max. Cable Length	3 m
	Data Rate	10 Gbps
	Conductor	Silver Plated Copper
Physical & Environment	Operating Temperature	0˚C to 70˚C (32˚F to 158˚F)
	Storage Temperature	-40˚C to 80˚C (-40˚F to 176˚F)
	Operating Humidity	10% to 90% RH non-condensing
	Storage Humidity	5% to 90% RH non-condensing

Some models featured in this guide may be unavailable in your country or region. Visit the Omada by TP-Link website for local sales information: https://www.omadanetworks.com. Specifications are subject to change without notice.
© 2025 TP-Link